

Essentials 1.8m Acrylic Pedestal

Combines simplicity and reliability for a attractive, affordable anti-theft solution.

The Essentials 1.8m Acrylic Pedestal combines simplicity with reliable performance to deliver an affordable, attractive anti-shoplifting solution. Constructed from high-grade, durable acrylic, this pedestal provides a transparent, sophisticated look at store entrances. The on-board electronics are contained within the base cover of the primary pedestal, eliminating the need for an external controller, and reducing installation and maintenance costs. To support green initiatives, this system uses less than 50W of energy per hour to help lower energy costs while supplying EAS protection for wider exits up to 3.6m (11.81ft). The integrated alarm located in the base of the primary pedestal uses a distinguished audible alarm to notify store personnel if protected merchandise passes through the detection zone. Each pedestal also fully illuminates with a blue (standard) or red (optional) illumination scheme for visual notification and deterrence during an alarm event.

Through system configuration, "Tags-too-Close" is an offered feature developed to help store associates better manage merchandising of tagged goods at the

front of the store. This feature helps reduce unnecessary and costly service calls and decreases nuisance alarms to enhance the shopper experience.

This pedestal provides in-store EAS Intelligence when connected to a compatible data management device to better manage store operations.

Retailer Values

- // Ideal for protecting wider exits up to 3.6m (11.81ft), maximizing customer flow
- // Modern, transparent design compliments any store setting
- // Each pedestal provides a unique blue (standard) or red (optional) illumination scheme for visual notification of alarm events
- // Integrated audible alarm notifies store associates of alarm events
- // EAS Intelligence option allows delivery of in-store operational information to better manage loss prevention and store operation efforts
- // "Tags-too-Close" feature helps reduce unnecessary and costly service calls and helps manage merchandising of tagged products at the store front
- // Service connection port allows full system software control at any antenna, helping reduce in-store service time

Product Compatibility

- Sensormatic AM Sensors
- Digital Remote Alarm
- Local Device Manager II (LDM II)
- UltraLink

Specifications

- Height** 145cm (4.75ft)
- Width** 35.6mm (1.4in)
- Thickness/Depth** 2.1cm (0.83in)
- Base Thickness 10.9cm (4.3in)

Electrical

Transmitter

- Operating Frequency 58kHz (+200Hz)
- Transmit Burst Duration 1.6ms
- Transmit Current 34.4A (in Tx coil) peak
- Transmit Current 15.2A peak (in Interconnect cable)

Burst Repetition Rate

- Based on 50Hz ac 37.5Hz
- Based on 60Hz ac 45Hz
- Antenna Coil Resistance 0.1 ohms (@58kHz)

Receiver

- Center Frequency 58kHz

Alarm

- Audio Level 83dB(A)

Environmental Constraints

Ambient Temperature

0°C to 40°C (32°F to 104°F)

Relative Humidity

0 to 90%, non-condensing

Enclosure

IPX0

Evaluated for altitudes less than 2000m (6500ft)

Declarations

EMC

47 CFR, Part 15

EN 300 330

EN 301 489

RSS-210

Safety


IEC 60950-1

CE This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.


Configuration

Measurements - meters (feet)

Dual



Split



Product Codes	Single-Level Primary Antenna(s)	Single-Level Secondary Antenna(s)	Dual Pedestal Antenna(s) (CFG)	Split Pedestal Antenna(s) (CFG)	Optional LED Kit, Red
ZS1150-P2 Secondary antenna required	●				
ZS1150-S2 Primary antenna required		●			
ZA1150-2			●		
ZA1150-3				●	
0352-0507-01					●

